

Domestic equipment & general tooling

- Ventilation..... 474
- Cooling..... 475
- Air purification..... 475
- Humidification - Dehumidification..... 476
- Heating..... 476
- Washroom..... 478
- Cleaning..... 479
- Compressed air equipment..... 480
- Power generator..... 480

What's new!

Mobile air conditioner



p. 475

Mobile fan - Mister



p. 475

Dehumidifiers



p. 476

High pressure cleaner



p. 479

Soap & gel dispenser



p. 478

Hand dryers



p. 478

Air compressors



p. 480

Power generator



p. 480



Adjustable head - 90° automatic oscillation - Removable protection grid - Infrared remote control for wall type - Light grey colour - 3 speed motor - 230V AC - Insulation class II - 140 to 180 cm adjustable height for pedestral fan.

Adjustable fans

	max. air flow (m³/h)	power (W)	sound power (Lw dB(A))	wire length (m)	IP	code
desk	2 400	35	50,8	1,8	-	VT2400
	4 000	40	57,2	1,8	-	VT4000
pedestral	4 000	40	57,2	3	-	VC4000
wall	2 400	35	50,8	-	20	VM2400
	4 000	40	57,2	-	20	VM4000



Adjustable head & closed position for easy storage - 3 speed - Automatic oscillation - 1 to 7 hour programmable stop - Touch control - Infrared remote control - ABS housing - 230V AC - Insulation class II - 1,7 m wire - Max. air flow 828 m³/h - Power consumption 42 W.

Oscillating fan

code
VTN0800

NEW

Galvanised carbon steel pales with white rustproof epoxy coating - ABS anti-UV plastic parts - 230V AC - Insulation class I - Reversible motor - Stem 375 mm - Optional infrared remote control & built-in light.

Reversible remote control indoor ceiling fan



blade diameter (cm)	flow (m³/h)	max. rotation min ⁻¹	speed power (W)	sound power (Lw dB(A))	code
90	11 590	200	70	46,1	VPNE090
120	13 810	200	70	49,1	VPNE120
140	16 580	200	70	52,6	VPNE140
160	17 010	200	70	55,6	VPNE160

Translucent light set

Energy saving bulb E27 max. 15 W & 165 mm (x 2 bulbs).

code
KLVP



Infrared remote control set

2 parts (transmitter & receiver) for speed & light control - AAA LR03 battery not included.

code
TIRVP

Stem

	code
Length 200 mm	TVP020
Length 500 mm	TVPB500E
Length 750 mm	TVP075
Length 1000 mm	TVP100

Speed variator

5 speeds - On/off - Reversible - For 1 device.



code
SVP100



VS10800

Big diameter for steady & powerful blowing - Attractive design - Robust carbon steel tubes - 360° orientation - 2 or 3 speed motor - 230V AC - Insulation class I - Rotary switch - 1,9 m wire.

Heavy duty fan

max. air flow (m³/h)	power (W)	sound power (Lw dB(A))	diameter (mm)	code
8 100	85 - 110	67,5	650	VS8100
10 800	190 - 250	75	735	VS10800



NEW

4 modes: automatic, cold, ventilation, dehumidification - ABS housing - 1,5 m & Ø 140 mm drainage hose - R290 refrigerant - 3 speed motor - Infrared remote control - 4 anti-dust washable air filters & 1 activated carbon filter - Anti-bacterious condensates tank - 230V AC - Insulation class I - Temperature range: 18 to 35°C - Drainage set for sliding window.

Mobile air conditioner

flow (m³/h)	sound pressure (Lp at 3m dB(A))	cooling capacity (W)	heating capacity (W)	room volume (m³)	code
360	44,5	2 600	1 000	90	CM2600

High thermal power for large rooms - 4 modes: automatic, cold, ventilation, dehumidification - ABS housing - 1,5 m & Ø 140 mm drainage hose - R290 refrigerant - 3 speed motor - Rotating compressor - Infrared remote control - 4 anti-dust washable air filters & 1 activated carbon filter - Anti-bacterious condensates tank - 230V AC - Insulation class I - Temperature range: 18 to 35°C - Drainage set for sliding window.

Mobile air conditioner - High thermal power

flow (m³/h)	sound pressure (Lp at 3m dB(A))	cooling capacity (W)	heating capacity (W)	room volume (m³)	code
495	42,5	3 200	-	120	CM3200
* 495	42,5	3 220	2700	120	CMR3200
430	43,5	3 700	-	140	CM3800
* 430	43,5	3 700	3 000	140	CMR3800

* Hot mode additionally.

Door leaf window set



code
KCM

NEW

3 level ultrasonic cooling technology - Air ionisation electrode - Insecticide - IceX function for performance enhancing with slab of ice - Infrared remote control - Timer & night mode - ABS black housing - 5 blades with 450 mm diameter - 3 speed ventilation - Digital pad - IP20 - Insulation class II.

Mobile fan - Mister

room volume (m³)	mist flow (ml/h)	air flow (m³/h)	power (W)	tank volume (l)	code
250	220	3 100	90	3,1	BRUM200

Air purification



NEW

Electrostatically charged filter - High level of filtration, class e2F - Easy filter cleaning - ABS white UV-resistant housing - 3 speed motor, with 12V DC (low tension) - 230V AC - On/off function & 3 speed selection - Insulation class II.



Air purifier - Domestic use

power (W)	room volume (m³)	code
2,4	30	PUR20
5,3	50	PUR30



For PUR20
For PUR30

Filter

code
FPUR20
FPUR30

NEW

4 stage high filtration level (washable polyurethane polyester pre-filter, class E10 HEPA filter, electrostatically charged filter, ionisation electrode) - Robust & silent device - Thermoplastic anti-chock light grey resin housing - Self-lubricated bearing motor on 3 speed antivibration stem - 230V AC - On/off function & 3 speed selection - Adjustable base for vertical mounting - Insulation class II.



Air purifier - Professional use

power (W)	room volume (m³)	sound power (dB(A))	code
30	45	53	PUR45
30	70	54	PUR70



For PUR45
For PUR70

Filter

code
FPUR45
FPUR70



Wall mounting set

code
KMPUR70

NEW

4 stage high filtration level (aluminium mesh pre-filter, electrostatic filter with electronic control, active carbon filter, ionisation electrode) - Robust & silent device - Thermoplastic anti-chock black resin housing - Self-lubricated bearing motor on 3 speed antivibration stem - 230V AC - On/off function & 3 speed selection - Adjustable base for vertical mounting - Insulation class II.



Air purifier - Professional use - Big volume

power (W)	room volume (m³)	sound power (dB(A))	code
36	100	55	PUR100



Active carbon filter

code
FPUR100



Wall mounting set

code
KMPUR70



NEW



Silent ultrasonic device - Aromatic essences 4 litre tank - 2 powers - Hourly programmable humidity rate setting - ABS white housing - Digital touch control panel (On/off, humidification power 210 ml/h / 350 ml/h, ambient humidity 40 / 50 / 60 / 70% HR or continuous, hourly timer up to 12 h, cool or lukewarm steam, night mode) - Water filter - Built-in lack of water protection - 230V AC - Insulation class II.

Ultrasonic humidifier - Domestic use

humidification capacity (ml/h)	power (W)	sound pressure (Lp dB(A) at 1m)	tank (l)	code
350	95	45	4	HM350

Robust construction - 2 speed ventilation for DME20 - Surrounding humidity display - Programmable humidity rate setting - ABS housing with handles - Rotating compressor with automatic shut-off protection - R290 refrigerant - Anti-frost thermostat - Tank overflow protection - Anti-bacterious removable tank - Anti-dust washable filter & activated carbon filter - 230V AC - Insulation class I - Temperature use: 5 to 32°C.

Mobile thermodynamic dehumidifier

room volume (m³)	sound pressure (Lp at 1m dB(A))	condensate water volume at 30°C 80% HR (l/day)	power (W)	tank (l)	code
60	42,2	10	290	2,5	DME10
100	42	14	280	2,5	DME14
120	45,8	20	390	3	DME20



DME10 & DME14

DME20

NEW



Easy to carry - Tank overflow protection & water level detection - 24 h timer - Ergonomic interface - Automatic defrost - Air intake washable filter - Laquered carbon steel housing - 230V AC - Cooling circuit R410A - Compressor - Water tank for DMI50 - Condensates drainage hose, Ø 12 mm & 1 m length - IP22 - Sound level 55/60 dB(A) - Insulation class I - Temperature range: 5 to 35°C.

Dehumidifier - Construction site

room volume (m³)	condensate water volume at 30°C 80% HR (l/day)	air flow (m³/h)	power (W)	tank (l)	code
300	50	350	700	7	DMI50
400	80	400	1 000	-	DMI80

Heating



1 000W & 2 000W heating modes & ventilation mode - Polypropylene housing - 230V AC - 3 m wire - Electric resistor with manual override - PTC limiter - Thermostat & antifrost function - IP21 - Insulation class II.

Portable blowing heater

	code
Standard	RSP2000
Daily programmable	RSPT2000

NEW



800 / 1 200 / 2 000W heating modes - Carbon steel housing - 15 mn hourly or daily setting - Roll-over protection - 230V AC - 1,5 m electric cable - Mica sheet with thermostatic protection electric resistance - Mechanical room thermostat - IP20 - Insulation class I - Fireproof reinforced nylon centrifugal blower.

Portable blowing heater - With timer

code
RSST2001

3 power convector & blowing radiator: 800W, 1 200W, 2 000W - Carbon steel housing - 230V AC - 1,6 m wire - Electric resistance with thermostatic protection - Thermostat & anti-frost function - IP20 - Insulation class II - Polypropylene centrifugal fan coil.

Convector 2 000W

code
CS2000

Blowing radiator

code
RSS2000

Programmable blowing radiator

code
RSST2000

Wall support set

code
KMCS





Height installation for downwards blowing - Motorised oscillating blowing - Hourly & weekly programming - Window opening automatic detection - Infrared remote control - Built-in digital thermostat - White ABS housing - Tangential ventilator - 230V AC - PTC ceramic heating construction - 1 000W & 2 000W power - Overheating protection - Insulation class II - IP22 - Air flow 150 m³/h - Room volume 60 m³.

Wall blowing heater

code
RSPL2000

Radiant heating

Complete set with pole, table & foot - Aluminium pole - IP65 - 3 heat lamps - 230V AC or 400V AC - Power: 3 x 1 500W - One electric connection.



Complete set

code
KPALO

Heat lamp



code
RE1501

Remote control



code
CADP



Wall support for 1 device

code
SUPMUR



Hanging support for 2 devices

In-line
Overlapped

code
SUPMURX2V
SUPMURX2H



Overlapped

Mobile heating unit - Electric

Includes wire, adjustable thermostat, fan & overheat thermal protection - 230V AC - IPX4 for 3 000W.



heating capacity (W)	air flow (m ³ /h)	surface (m ²)	pack	code
2 000	171	25	8	AME02C
3 000	354	30	8	AME03
3 000	420	40	6	AME03T

Mobile heating unit - Gas (butane or propane)

Includes wire, overheat thermal protection, gas shut-off safety, flexible hose & gas pressure regulator - Gas cylinder: not supplied - 230V AC.



heating capacity (W)	air flow (m ³ /h)	surface (m ²)	code
15 000	320	150	AMG15
30 000	650	300	AMG30

Mobile heating unit - Gas oil

Includes wire, adjustable thermostat, overheat thermal protection, automatic shut-off safety, galvanised carbon steel tank & wheels - 230V AC.



heating capacity (W)	air flow (m ³ /h)	surface (m ²)	code
30 000	850	300	AMF30



NEW

Liquid soap & hydroalcoholic gel automatic dispenser with touchless infrared detection - Adjustment of the delivered dose for each use during the installation - Remaining quantity indicator - Anti-UV resistant ABS cover - 230V AC - Power 6 W, stand-by mode 0,38 W - Peristaltic pump - Removable 0,5l PEHD soap tank - IPX4 - Shock resistance index IK9 - Class insulation II.

Soap & gel automatic dispenser

code
DSAVONGEL



NEW

Ultra-fast drying time & low electric consumption - Intensive use - Anti-dust air filter - Water recovery tank - Germicidal UV lamp - ABS housing - 230V AC - Heating power 1 850 W - DC EC motor - Air flow 350 m³/h - IPX4 - Insulation class I - Automatic switch-on with delay - Diffusion by pulsating nozzles - Sound pressure Lp = 76 dB(A) at 1 m.

Forced-air & water recovery automatic hand-dryer

	code
White	SMSUB
Grey	SMSUG



NEW

Ultra-fast drying time & low electric consumption - Dirty filter detection light - Stainless steel cover - Antivibration resin base - Air outlet speed 100 m/s - AC motor (SMEB) & EC motor (SMESN) 30 000 turn/mn - Touchless infrared detection with automatic start & stop - Overuse safety with 50 s shut off - HEPA filter with cleanable and replaceable suction (for SMESN) - 230V AC - IPX4 - Insulation class I.

Forced-air automatic hand-dryer

motor	air flow (m ³ /h)	total consumption (W)	motor consumption (W)	sound pressure (dB(A) Lp at 1 m)	code
AC	90	800	400	70	SMEBAX
EC	81	700	300	70	SMESN



NEW

ABS nozzle with ergonomic wet hand shape - Longlasting magnetic hanging system - PU spiral hose with thermo-insulated protection coating - Timer in case of overuse - ABS cover & inner parts - Automatic start when unhooking - 2 speed axial motor-fan - 230V AC - Air flow 42 m³/h - Sound pressure Lp = 70 dB(A) at 1 m - IP24 - Insulation class II.

Extensible magnetic hose hair-dryer

code
SCV



NEW

Self-extinguishing ABS cover - Ergonomic design - Heater thermal resistance protection - On/off power switch on wall support - Direct current 2 speed motor - Built-in support safety switch - 230V AC - IP20 - Insulation class II.

Wall-mounted hair-dryer

air flow (m ³ /h)	total consumption (W)	motor consumption (W)	sound pressure (dB(A) Lw)	code
81	1 200	20	70	SCP1200
81	1600	20	70	SCP1600



Dust, liquid & solid vacuum cleaning - Polypropylene body - Tight switch - Thermal circuit breaker - PE cartridge filter - Washable anti-clogging membrane pre-filter - Includes accessories (see picture below).

Vacuum cleaner

power (W)	tank (l)	depression (mmH ₂ O / kPa)	sound pressure (Lp dB(A) at 1m)	flow (l/s)	code
1 000	27	1850/18,5	76,8	64	ASPI27
1 000	35	1850/18,5	76,8	64	ASPI35
1 000	35	2300/23	73,4	55	ASPI35P

* With electric socket for power tools with automatic control.



Accessories set

code
KASPI

Spare cartridge filter

code
FASPI25
FASPI35P

NEW



Dust, liquid & solid vacuum cleaning - 5 m wire - Blower function - Includes cartridge filter, 2 m hose, wet or dry floor brush, crevice nozzle.

Vacuum cleaner - Professional use

power (W)	tank (l)	depression (kPa)	flow (l/s)	code
1 600	35	20	39	559016035



NEW



Longlasting use - Induction motor - Brass body pump - Stainless steel pistons - Anti-twist 10 m hose with built-in reel - Power 2 500W - Max. power 150 bar (450 l/h), max. usable power 130 bar (400 l/h) - Includes accessories (see picture).

Electric high pressure cleaner

code
559015125

NEW



Sustained use - Honda 4,8 hp petrol engine - Brass body pump - Stainless steel pistons - Metal reinforced PVC hose 8 m - Tank 3,1 l - 2h15mn endurance - Max. power 210 bar (690 l/h), max. usable power 170 bar (600 l/h) - Sound level 103 dB(A) - Weight 30 kg - Includes spray gun & 4 nozzles.

Thermal engine high pressure cleaner

code
559017948



NEW **Air compressor - Horizontal**
6 l tank - 1,5 hp - Max. pressure 8 bar -
Supplied without accessories.

code
559010150



34 pc pneumatic accessories set
Reinforced case including: square 1/2" impact wrench, ratchet wrench, hammer, chisel, straight grinder with 3 chisels, empty oil can, grinding wheels, coupling sleeve, assembly wrench.

code
559011534



Air compressor - Vertical
24 l tank - 1,5 hp - Max. pressure 10 bar -
Supplied without accessories.

code
559010152



8 pc pneumatic accessories set
Includes: gravitational painting gun 0,5 l, nylon hose 5 m, blowgun, inflating handle, spray gun 1l.

code
559011508



Pneumatic hose 6 x 11 mm
Braided with end pieces 7,5 m -
Max. pressure 10 bar.

code
559011008



Pneumatic dispenser
For mastic & silicone universal cartridge 300 ml.

code
559011573



Reel 20 m
Pneumatic hose 6 x 12 mm -
Max. pressure 10 bar.

code
559011020



8 pc inflating nozzle set

code
559011536

Power generator

NEW

4-stroke engine, 210 cm³, power 7 hp, tank 15 l - Start-up at launcher - 100 % copper alternator - Max. power 3 100W - 3 230V ports + 1 USB 5V port - Automatic voltage regulator, compatible with electronic devices - 2 wheel cart & handling arm - 10 h endurance - Sound level 96 dB(A) - Weight 66 kg.



Thermal engine power generator - Construction site

code
559010155