

Domestic equipment & general tooling

- Heating..... 482
- Cooling..... 483
- Ventilation..... 484
- Humidification - Dehumidification..... 485
- Air purification..... 485
- Hygiene..... 486
- Cleaning..... 487
- Compressed air equipment..... 488
- Power generator..... 488

What's new!

Portable blowing heaters



p. 482

Wall blowing heaters



p. 479

Towel-dryer



p. 486

Air compressor



p. 488



Mobile heating unit - Electric

Includes wire, adjustable thermostat, fan & overheat thermal protection - 230V AC - IPX4 for 3 000W.



heating capacity (W)	air flow (m³/h)	surface (m²)	pack	code	price €
2 000	171	25	8	AME02C	
3 000	354	30	8	AME03	
3 000	420	40	6	AME03T	

Mobile heating unit - Gas (butane or propane)

Includes wire, overheat thermal protection, gas shut-off safety, flexible hose & gas pressure regulator - Gas cylinder: not supplied - 230V AC.



heating capacity (W)	air flow (m³/h)	surface (m²)	code	price €
15 000	320	150	AMG15	
30 000	650	300	AMG30	

Mobile heating unit - Gas oil

Includes wire, adjustable thermostat, overheat thermal protection, automatic shut-off safety, galvanised carbon steel tank & wheels - 230V AC.



heating capacity (W)	air flow (m³/h)	surface (m²)	code	price €
30 000	850	300	AMF30	

NEW Portable blowing heater

1 000W & 2 000W heating modes - Polypropylene body - 230V AC - Thermostat - Overheating electric protection - IP21 - Insulation class II - For RSPT2001: LCD screen control, infrared remote control, automatic oscillation, programmable timer, anti-dust filter.



RSP2001



RSPT2001

	code	price €
Standard	RSP2001	
Daily programmable	RSPT2001	

Portable blowing heater - With timer

800 / 1 200 / 2 000W heating modes - Carbon steel housing - 15 mn hourly or daily setting - Roll-over protection - 230V AC - 1,5 m electric cable - Mica sheet with thermostatic protection electric resistance - Mechanical room thermostat - IP20 - Insulation class I - Fireproof reinforced nylon centrifugal blower.



code	price €
RSST2001	

Convector 2 000W

3 power convector & blowing radiator: 800W, 1 200W, 2 000W - Carbon steel housing - 230V AC - 1,6 m wire - Electric resistance with thermostatic protection - Thermostat & anti-frost function - IP20 - Insulation class II - Polypropylene centrifugal fan coil.



code	price €
CS2000	

Blowing radiator

code	price €
RSS2000	

Programmable blowing radiator

code	price €
RSST2000	

Wall support set

code	price €
KMCS	



NEW Wall blowing heater



Height installation for downwards blowing - Motorised oscillating blowing - Window opening automatic detection - Infrared remote control - Built-in digital thermostat - Control: ventilator speed, temperature, fin blowing oscillation - White ABS housing - Tangential ventilator - 230V AC - PTC ceramic heating construction - 1 000W & 2 000W heating modes & ventilation mode - Overheating protection - Insulation class II - IP22 - Tuya smart wifi connection.

code	price €
RSPL2000	

NEW Wall radiant heater



Directional radiant heating - Silent - Anti-water protection - 600W, 1 200W & 1 800W heating modes - Carbon steel housing - 230V AC - Infrared lamp electric resistance - String switch - IPX4 - Insulation class I.

code	price €
RID1800	
RI1800	



Cooling



Mobile air conditioner

4 modes: automatic, cold, ventilation, dehumidification - ABS housing - 1,5 m & Ø 140 mm drainage hose - R290 refrigerant - 3 speed motor - Infrared remote control - 4 anti-dust washable air filters & 1 activated carbon filter - Anti-bacterious condensates tank - 230V AC - Insulation class I - Temperature range: 18 to 35°C - Drainage set for sliding window.

flow (m³/h)	sound pressure (Lp at 3m dB(A))	cooling capacity (W)	heating capacity (W)	room volume (m³)	code	price €
360	44,5	2 600	1 000	90	CM2600	



Mobile air conditioner - High thermal power

High thermal power for large rooms - 4 modes: automatic, cold, ventilation, dehumidification - ABS housing - 1,5 m & Ø 140 mm drainage hose - R290 refrigerant - 3 speed motor - Rotating compressor - Infrared remote control - 4 anti-dust washable air filters & 1 activated carbon filter - Anti-bacterious condensates tank - 230V AC - Insulation class I - Temperature range: 18 to 35°C - Drainage set for sliding window.

flow (m³/h)	sound pressure (Lp at 3m dB(A))	cooling capacity (W)	heating capacity (W)	room volume (m³)	code	price €
495	42,5	3 200	-	120	CM3200	
* 495	42,5	3 220	2700	120	CMR3200	
430	43,5	3 700	-	140	CM3800	
* 430	43,5	3 700	3 000	140	CMR3800	

* Hot mode additionally.



Door leaf window set



code	price €
KCM	

Mobile fan - Mister

3 level ultrasonic cooling technology - Air ionisation electrode - Insecticide - IceX function for performance enhancing with slab of ice - Infrared remote control - Timer & night mode - ABS black housing - 5 blades with 450 mm diameter - 3 speed ventilation - Digital pad - IP20 - Insulation class II.

room volume (m³)	mist flow (ml/h)	air flow (m³/h)	power (W)	tank volume (l)	code	price €
250	220	3 100	90	3,1	BRUM200	



Adjustable fans

Adjustable head - 90° automatic oscillation - Removable protection grid - Infrared remote control for wall type - Light grey colour - 3 speed motor - 230V AC - Insulation class II - 140 to 180 cm adjustable height for pedestral fan.

	max. air flow (m³/h)	power (W)	sound power (Lw dB(A))	wire length (m)	IP	code	price €
desk	2 400	35	50,8	1,8	-	VT2400	
	4 000	40	57,2	1,8	-	VT4000	
pedestral	4 000	40	57,2	3	-	VC4000	
wall	2 400	35	50,8	-	20	VM2400	
	4 000	40	57,2	-	20	VM4000	

Oscillating fan

Adjustable head & closed position for easy storage - 3 speed - Automatic oscillation - 1 to 7 hour programmable stop - Touch control - Infrared remote control - ABS housing - 230V AC - Insulation class II - 1,7 m wire - Max. air flow 828 m³/h - Power consumption 42 W.

code	price €
VTN0800	



Reversible remote control indoor ceiling fan

Galvanised carbon steel pales with white rustproof epoxy coating - ABS anti-UV plastic parts - 230V AC - Insulation class I - Reversible motor - Stem 375 mm - Optional infrared remote control & built-in light.

blade diameter (cm)	flow (m³/h)	max. rotation min ⁻¹	speed power (W)	sound power (Lw dB(A))	code	price €
90	11 590	200	70	46,1	VPNE090	
120	13 810	200	70	49,1	VPNE120	
140	16 580	200	70	52,6	VPNE140	
160	17 010	200	70	55,6	VPNE160	



Translucent light set

Energy saving bulb E27 max. 15 W & 165 mm (x 2 bulbs).

code	price €
KLVP	



Infrared remote control set

2 parts (transmitter & receiver) for speed & light control - AAA LR03 battery not included.

code	price €
TIRVP	



Stem

	code	price €
Length 200 mm	TVP020	
Length 500 mm	TVPB500E	
Length 750 mm	TVP075	
Length 1000 mm	TVP100	

Speed variator

5 speeds - On/off - Reversible - For 1 device.

code	price €
SVP100	



Heavy duty fan

Big diameter for steady & powerful blowing - Attractive design - Robust carbon steel tubes - 360° orientation - 2 or 3 speed motor - 230V AC - Insulation class I - Rotary switch - 1,9 m wire.

max. air flow (m³/h)	power (W)	sound power (Lw dB(A))	diameter (mm)	code	price €
8 100	85 - 110	67,5	650	VS8100	
10 800	190 - 250	75	735	VS10800	



VS10800



Ultrasonic humidifier - Domestic use

Silent ultrasonic device - Aromatic essences 4 litre tank - 2 powers - Hourly programmable humidity rate setting - ABS white housing - Digital touch control panel (On/off, humidification power 210 ml/h / 350 ml/h, ambient humidity 40 / 50 / 60 / 70% HR or continuous, hourly timer up to 12 h, cool or lukewarm steam, night mode) - Water filter - Built-in lack of water protection - 230V AC - Insulation class II.

humidification capacity (ml/h)	power (W)	sound pressure (Lp dB(A) at 1m)	tank (l)	code	price €
350	95	45	4	HM350	



Mobile thermodynamic dehumidifier

Robust construction - 2 speed ventilation for DME20 - Surrounding humidity display - Programmable humidity rate setting - ABS housing with handles - Rotating compressor with automatic shut-off protection - R290 refrigerant - Anti-frost thermostat - Tank overflow protection - Anti-bacterious removable tank - Anti-dust washable filter & activated carbon filter - 230V AC - Insulation class I - Temperature use: 5 to 32°C.

room volume (m³)	sound pressure (Lp at 1m dB(A))	condensate water volume at 30°C 80% HR (l/day)	power (W)	tank (l)	code	price €
60	42,2	10	290	2,5	DME10	
100	42	14	280	2,5	DME14	
120	45,8	20	390	3	DME20	



Dehumidifier - Construction site

Easy to carry - Tank overflow protection & water level detection - 24 h timer - Ergonomic interface - Automatic defrost - Air intake washable filter - Laquered carbon steel housing - 230V AC - Cooling circuit R410A - Compressor - Water tank for DMI50 - Condensates drainage hose, Ø 12 mm & 1 m length - IP22 - Sound level 55/60 dB(A) - Insulation class I - Temperature range: 5 to 35°C.

room volume (m³)	condensate water volume at 30°C 80% HR (l/day)	air flow (m³/h)	power (W)	tank (l)	code	price €
300	50	350	700	7	DMI50	
400	80	400	1 000	-	DMI80	

Air purification



Air purifier - Domestic use



Electrostatically charged filter - High level of filtration, class e2F - Easy filter cleaning - ABS white UV-resistant housing - 3 speed motor, with 12V DC (low tension) - 230V AC - On/off function & 3 speed selection - Insulation class II.

power (W)	room volume (m³)	code	price €
5,3	50	PUR30	



Filter

code	price €
FPUR30	

Air purifier - Professional use



4 stage high filtration level (washable polyurethane polyester pre-filter, class E10 HEPA filter, electrostatically charged filter, ionisation electrode) - Robust & silent device - Thermoplastic anti-chock light grey resin housing - Self-lubricated bearing motor on 3 speed antivibration stem - 230V AC - On/off function & 3 speed selection - Adjustable base for vertical mounting - Insulation class II.

power (W)	room volume (m³)	sound power (dB(A))	code	price €
30	45	53	PUR45	
30	70	54	PUR70	



Filter

code	price €
FPUR45	
FPUR70	



Wall mounting set


code	price €
KMPUR70	

Air purifier - Professional use - Big volume



4 stage high filtration level (aluminium mesh pre-filter, electrostatic filter with electronic control, active carbon filter, ionisation electrode) - Robust & silent device - Thermoplastic anti-chock black resin housing - Self-lubricated bearing motor on 3 speed antivibration stem - 230V AC - On/off function & 3 speed selection - Adjustable base for vertical mounting - Insulation class II.

power (W)	room volume (m³)	sound power (dB(A))	code	price €
36	100	55	PUR100	



Active carbon filter

code	price €
FPUR100	



Wall mounting set

code	price €
KMPUR70	



Soap & gel automatic dispenser

Liquid soap & hydroalcoholic gel automatic dispenser with touchless infrared detection - Adjustment of the delivered dose for each use during the installation - Remaining quantity indicator - Anti-UV resistant ABS cover - 230V AC - Power 6 W, stand-by mode 0,38 W - Peristaltic pump - Removable 0,5l PEHD soap tank - IPX4 - Shock resistance index IK9 - Class insulation II.

code	price €
DSAVONGEL	



Forced-air & water recovery automatic hand-dryer

Ultra-fast drying time & low electric consumption - Intensive use - Anti-dust air filter - Water recovery tank - Germicidal UV lamp - ABS housing - 230V AC - Heating power 1 850 W - DC EC motor - Air flow 350 m³/h - IPX4 - Insulation class I - Automatic switch-on with delay - Diffusion by pulsating nozzles - Sound pressure Lp = 76 dB(A) at 1 m.

White
Grey

code	price €
SMSUB	
SMSUG	



Forced-air automatic hand-dryer

Ultra-fast drying time & low electric consumption - Dirty filter detection light - Stainless steel cover - Antivibration resin base - Air outlet speed 100 m/s - AC motor (SMEB) & EC motor (SMESN) 30 000 turn/mn - Touchless infrared detection with automatic start & stop - Overuse safety with 50 s shut off - HEPA filter with cleanable and replaceable suction (for SMESN) - 230V AC - IPX4 - Insulation class I.

motor	air flow (m ³ /h)	total consumption (W)	motor consumption (W)	sound pressure (dB(A) Lp at 1 m)	code	price €
AC	90	800	400	70	SMEBAX	
EC	81	700	300	70	SMESN	



Extensible magnetic hose hair-dryer

ABS nozzle with ergonomic wet hand shape - Longlasting magnetic hanging system - PU spiral hose with thermo-insulated protection coating - Timer in case of overuse - ABS cover & inner parts - Automatic start when unhooking - 2 speed axial motor-fan - 230V AC - Air flow 42 m³/h - Sound pressure Lp = 70 dB(A) at 1 m - IP24 - Insulation class II.

code	price €
SCV	



Wall-mounted hair-dryer

Self-extinguishing ABS cover - Ergonomic design - Heater thermal resistance protection - On/off power switch on wall support - Direct current 2 speed motor - Built-in support safety switch - 230V AC - IP20 - Insulation class II.

air flow (m ³ /h)	total consumption (W)	motor consumption (W)	sound pressure (dB(A) Lw)	code	price €
81	1 200	20	70	SCP1200	
81	1600	20	70	SCP1600	



NEW Electric wall blowing towel-dryer

Blowing heating - Wall installation - Digital panel - Infrared remote control - Window opening automatic detection - Hourly & weekly programming - White ABS cover - Black polycarbonate body - Adjustable downwards blowing grille - 230V AC - Overheating protection - Polyurethane anti-dust filter - IP23 - Insulation class II.

code	price €
SSV1500	



Vacuum cleaner

Dust, liquid & solid vacuum cleaning - Polypropylene body - Tight switch - Thermal circuit breaker - PE cartridge filter - Washable anti-clogging membrane pre-filter - Includes accessories (see picture below).

power (W)	tank (l)	depression (mmH ₂ O / kPa)	sound pressure (Lp dB(A) at 1m)	flow (l/s)	code	price €
1 000	27	1850/18,5	76,8	64	ASPI27	
1 000	35	1850/18,5	76,8	64	ASPI35	
1 000	35	2300/23	73,4	55	ASPI35P	

* With electric socket for power tools with automatic control.



Accessories set

code	price €
KASPI	

Spare cartridge filter

code	price €
FASPI25	
FASPI35P	



Vacuum cleaner - Professional use

Dust, liquid & solid vacuum cleaning - 5 m wire - Blower function - Includes cartridge filter, 2 m hose, wet or dry floor brush, crevice nozzle.

power (W)	tank (l)	depression (kPa)	flow (l/s)	code	price €
1 600	35	20	39	559016235	



Electric high pressure cleaner

Longlasting use - Induction motor - Brass body pump - Stainless steel pistons - Anti-twist 10 m hose with built-in reel - Power 2 500W - Max. power 150 bar (450 l/h), max. usable power 130 bar (400 l/h) - Includes accessories (see picture).

code	price €
559015125	



Thermal engine high pressure cleaner

Sustained use - Honda 4,8 hp petrol engine - Brass body pump - Stainless steel pistons - Metal reinforced PVC hose 8 m - Tank 3,1 l - 2h15mn endurance - Max. power 210 bar (690 l/h), max. usable power 170 bar (600 l/h) - Sound level 103 dB(A) - Weight 30 kg - Includes spray gun & 4 nozzles.

code	price €
559017948	



Air compressor - Horizontal
6 l tank - 1,5 hp - Max. pressure 8 bar -
Supplied without accessories.

code	price €
559010150	



Pneumatic accessories set (34 pieces)
Reinforced case including: square 1/2" impact wrench, ratchet wrench, hammer, chisel, straight grinder with 3 chisels, empty oil can, grinding wheels, coupling sleeve, assembly wrench.

code	price €
559011534	



Air compressor - Vertical
24 l tank - 1,5 hp - Max. pressure 10 bar -
Supplied without accessories.

code	price €
559010152	



Pneumatic accessories set (8 pieces)
Includes: gravitational painting gun 0,5 l, nylon hose 5 m, blowgun, inflating handle, spray gun 1l.

code	price €
559011508	



NEW

Air compressor - Vertical
50 l tank - 2 hp - Max. pressure 10 bar - Air flow 3 bar: 140 l/mm -
Air flow 7 bar: 126 l/mm - Built-in filter.

code	price €
559010202	



Pneumatic hose 6 x 11 mm
Braided with end pieces 7,5 m -
Max. pressure 10 bar.

code	price €
559011008	



Pneumatic dispenser
For mastic & silicone universal cartridge 300 ml.

code	price €
559011573	



Reel 20 m
Pneumatic hose 6 x 12 mm -
Max. pressure 10 bar.

code	price €
559011020	



Inflating nozzle set (8 pieces)

code	price €
559011536	

Power generator

Thermal engine power generator - Construction site

4-stroke engine, 210 cm³, power 7 hp, tank 15 l - Start-up at launcher - 100 % copper alternator - Max. power 3 100W - 3 230V ports + 1 USB 5V port - Automatic voltage regulator, compatible with electronic devices - 2 wheel cart & handling arm - 10 h endurance - Sound level 96 dB(A) - Weight 66 kg.



code	price €
559010155	